

34600 Commerce Road Fraser, Michigan 48026

PH: (586) 296-5900

FAX: (586) 296-5836

TRINCO™ MASTER MODEL 60X48SL/600RC WITH 600 CFM ABRASIVE SEPARATOR

- Ruggedly built of 14 Gauge welded steel
- Spring counter-balance assembly for hinged top
- Double floor 1/8" Expandex steel plus Carbon screen
- Trinco™ Tungsten carbide nozzle
- Trinco™ safety enclosed floor valve blasting control
- Trinco™ fluorescent lighting to eliminate shadows and minimize energy usage
- Trinco™ large 12"x24" safety glass window for excellent visibility and increased operator efficiency
- Air pressure regulator and gauge
- Trinco[™] easy change window frames
- Trinco™ Neoprene gloves
- Trinco™ Large side door 20" x 36

Inside

ator and ga nge window e gloves e door - 20"	frames		
Depth Width Height	48" 60" 31"		

Overall

Depth 74" Completely open 80"

Width 77" Height 71"

Door Openings

Two (2)

Flip Top 60" x 48" Side Door 20" x 36"

Total Shipping Weight

947 Lbs.

OPTIONAL ACCESSORIES:

Auto Power Basket

Turntable

Spare Parts package

Abrasives

TRINCO™ DRY BLAST APPLICATIONS

The applications of Trinco™ Cabinets are virtually limitless - cleaning, deburring, decorating, deflashing, etching, finishing, honing, peening, etc. All of these uses and more con be accomplished easily with quick sweeps of the gun nozzle. Scale, corrosion, old paint and other surface materials are removed in minutes leaving metal surfaces free of foreign matter and contamination. Even tough mill scale is quickly and efficiently removed.

The usual operating pressure for the Trinco™ Dry Blast Cabinets is 85 PSI. The equipment utilizes a variety of abrasives such as Trin Mixes™, glass beads, aluminum oxide, silicon carbide, nut shells, etc. A multitude of finishes are possible ranging from a micro-finish to a coarse-grade finish depending upon the specific media used. Trinco™ Cabinets can apply the proper abrasive to provide the desired finish for each specific application.

web: www.trinco.com Revised 4/02