

34600 Commerce Road Fraser, Michigan 48026

PH: (586) 296-5900

FAX: (586) 296-5836

TRINCO™ MASTER MODEL 42 X 24 SPLIT LEVEL WITH 450 CFM ABRASIVE SEPARATOR

- Ruggedly built of 14 Gauge welded steel
- Double floor 1/8" Expandex steel plus Carbon screen
- Trinco™ Tungsten carbide nozzle
- Trinco[™] safety enclosed floor valve blasting control
- Trinco™ fluorescent lighting to eliminate shadows
- Trinco™ large 12"x24" safety glass window for excellent visibility
- Air pressure regulator and gauge
- Trinco[™] filter bag
- Trinco[™] easy change window frame
- Trinco[™] heavyweight rubber gloves Neoprene optional

Inside:

Depth	24"
Width	42"
Height	24"



Two (2)

Flip Top 42" x 24" Side Door 11" x 11"

Shipping Weight: 557 Lbs.



NEVER USE SILICA-BASEDPRODUCTS IN TRINCO™BLAST SYSTEMS Ref. NIOSH Alert # 92-102

TRINCO™ DRY BLAST APPLICATIONS

The applications of Trinco™ Cabinets are virtually limitless - cleaning, deburring, decorating, deflashing, etching, finishing, honing, peening, etc. All of these uses and more con be accomplished easily with quick sweeps of the gun nozzle. Scale corrosion, old paint and other surface materials are removed in minutes leaving metal surfaces free of foreign matter and contamination. Even tough mill scale is quickly and efficiently removed.

The usual operating pressure for the Trinco™ Dry Blast Cabinets is 85 PSI. The equipment utilizes a variety of abrasives such as Trin Mixes™, glass beads, aluminum oxide, silicon carbide, nut shells, etc. A multitude of finishes are possible ranging from a micro-finish to a coarse-grade finish depending upon the specific media used. Trinco™ Cabinets can apply the proper abrasive to provide the desired finish for each specific application.

web: www.trinco.com - Rev 4/02