

Leader in Blast Cleaning Since 1951 34600 Commerce Road Fraser, Michigan 48026 PH: (586) 296-5900

FAX: (586) 296-5836

TRINCO™ MASTER MODEL 48 X 24 SPLIT LEVEL WITH 450 CFM ABRASIVE SEPARATOR

- Ruggedly built of 14 Gauge welded steel Double floor - 1/8" Expandex steel plus Carbon screen
- Trinco™ Tungsten carbide nozzle
- Trinco[™] safety enclosed floor valve blasting control
- Trinco™ fluorescent lighting to eliminate shadows
- Trinco™ large 12"x24" safety glass window
- Air pressure regulator and gauge
- Trinco[™] filter bag
- Trinco™ easy change window frame
- Trinco™ heavyweight rubber gloves Neoprene optional



Inside:

Depth 24" Width 48" Height 24"

Overall:

Depth 38" Completely open 50"

Width 76" Height 65"

Door Openings:

Two (2)

Flip Top 48" x 24" Side Door 11" x 11"

Shipping Weight: Approximately 760 Lbs. (includes separator)

Optional Accessories:

- Water Filter
- Blow Off Gun
- Turntable
- Auto Power Basket
- Spare parts package
- Abrasives

NEVER USE SILICA-BASEDPRODUCTS

IN TRINCO™BLAST SYSTEMS

Ref. NIOSH Alert # 92-102

TRINCO™ DRY BLAST APPLICATIONS

The applications of Trinco™ Cabinets are virtually limitless - cleaning, deburring, decorating, deflashing, etching, finishing, honing, peening, etc. All of these uses and more con be accomplished easily with quick sweeps of the gun nozzle. Scale corrosion, old paint and other surface materials are removed in minutes leaving metal surfaces free of foreign matter and contamination. Even tough mill scale is quickly and efficiently removed.

The usual operating pressure for the Trinco™ Dry Blast Cabinets is 85 PSI. The equipment utilizes a variety of abrasives such as Trin Mixes™, glass beads, aluminum oxide, silicon carbide, nut shells, etc. A multitude of finishes are possible ranging from a micro-finish to a coarse-grade finish depending upon the

specific media used. Trinco™ Cabinets can apply the proper abrasive to provide the desired finish for each specific application. web: www.trinco.com -

Rev 4/02